

## Receiver and Endcoder Modules

➤ **UFO 110/8 | 206500020**



### ➤ Features

- Input 8 channel DVB-S/S2/S2x FTA
- Occupies two slots
- Setup via web interface UFO 101

### ➤ Technical Data

Inputs		
Sat-IF input		8x F connectors, 75 Ω
Frequency range	MHz	950–2150
Signal level	dBm	-70~20
Roll off factor		0.15/0.20/0.25/0.35
DiSEqC™1.0		vert./horiz., low/high; sat. pos. (A/B/C/D)
Switching levels	V/kHz	14/18, 0/22
Remote feed current for LNB	mA	max. 400 (Independent for each LNB)
Demodulation DVB-S/S2/S2x		
Number of tuner		8
Compliance	DVB-S/S2/S2X	EN 300 421 / EN 302 307-1V1.4.1 / EN 302 307-2V1.1.1
Modulations-Standards	DVB-S	QPSK, 8PSK
	DVB-S2	QPSK, 8PSK, 16APSK, 32APSK
	DVB-S2X	QPSK, 8PSK, 16APSK, 32APSK, 64APSK
Symbol rate	DVB-S MS/s	1~45
	DVB-S2 MS/s	1~45
	DVB-S2S MS/s	1~34
FEC (Normal FEC FECFRAME)	DVB-S	1/2, 2/3, 3/4, 5/6, 7/8
	DVB-S2	1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
	DVB-S2X	11/15, 7/9, 4/5, 5/6
Power	W	30